



Govt. of India
Ministry of New & Renewable Energy
Solar Energy Centre
P.O. & Village Gwalpahari, Distt. Gurgaon
Haryana, India

2012-2013

TEST REPORT ON BATTERY

The Industry is the Manufacturers of Batteries

Sample ID No. 47/12/BT.


**Manufactured by : M/s Luminous Power Technologies Pvt. Ltd., C-8&C-9,
Community Centre, Janakpuri, New Delhi-110058**

**Submitted by : M/s Luminous Power Technologies Pvt. Ltd., C-8&C-9,
Community Centre, Janakpuri, New Delhi-110058**

This is a report on measurements of **Capacity rating, Charge efficiency And Self Discharge** carried out on the battery (sample no. 47/12/BT) submitted at Solar Energy Centre as per **IS 13369:1992** standards. The data reported in this TEST REPORT are valid at the time of and under the stipulated conditions of measurement and the test results are applicable to this battery only and do not apply to other batteries even though declared to be identical. The data contents in this report do not constitute a qualification test certificate. SEC does not accept any liability for any consequences including commercial or otherwise arising out of the utilization of the information contained in this report.

The Test Report, if reproduced for any purpose, commercial or otherwise, should be reproduced in full. The contents of the report can be published only after a written approval from the Adviser & Head, SEC. This report consists of 3 pages.

Kavish Selgal



Test Report No.	Total No. of pages	Page No.
47/12/BT/SEC	3	1

TEST REPORT OF LEAD ACID BATTERY


Sample ID No.47/12/BT

Manufactured by : M/s Luminous Power Technologies Pvt. Ltd., C-8&C-9,
Community Centre, Janakpuri, New Delhi-110058

Submitted by : M/s Luminous Power Technologies Pvt. Ltd., C-8&C-9,
Community Centre, Janakpuri, New Delhi-110058

S.No	Test Description	Manufacture's Claim	Observations	Remarks
1	(i) Brand (ii) Type (iii) S.No. (iv) Year (v) <u>Rating</u> (a) Voltage (b) Capacity at C10 discharge rate (vi) Dimension (mm) (vii) Weight before testing (kg)	LUMINOUS Lead Acid(LPT1275L) ABF2055051 2012 12V 75 Ah 505X220X292 36.3 Kg	LUMINOUS Lead Acid(LPT1275L) ABF2055051 2012 12V 90.19Ah 505X220X292 36.14Kg	cut off voltage 11.1V
2	Charging Efficiency: (A) Capacity on discharging at (C 10) constant current continuously up to cut off voltage. (B)Capacity after recharging the battery by 89.24Ah and then again discharging up to cut off voltage. (C) Charging efficiency		89.24Ah 82.23Ah 92.1 %	

Harsh Selgal




Test report No.	Total No. of pages	Page No.
47/12/BT/SEC	3	2

3	Self discharge test: (A) Initial Capacity on discharging at (C 10) constant current continuously up to cut off voltage. (B) Final Capacity after keeping 28 days in 27 ±5 deg.C temperature. (C) Discharge in %		80Ah 78.20Ah 2.25 %	
---	--	--	---	--

Prepared by: Hansh Selyal
Date: 24/09/12

Approved by: Prahaladmasu
Date: 24.9.12

S. M. D.
Issued by:
Date: 24/9/2012



Test report No.	Total No. of pages	Page No.
47/12/BT/SEC	3	3